



Declaration of Performance (DoP)

DoP Nº.: DP003 CIDAC / 2016-09-05
(According to Annex III of the Regulation (CE) n°305/2011)

Version 03 / September 2015

1. Product Name:

HIDROSTAN IN

Thicknesses (0.50, 0.75, 1.10) mm

2. Product Type:

Number allowing identification of the construction product as required under Article 11(4) of the CPR.

(Batch nº: see label and product)

3. Intended for use as anti-capillary barrier in buildings and the range of use is vapour control layer such as façade waterproofing or similar.

4. Name and registered trade name

CIDAC, S. COOP. R. L.

Carretera de Sant Joan Despí, 101 -103.
08940 Cornellà (Barcelona) SPAIN
Tel.: +34 933 772 262 / +34 933 772 405
Fax: +34 933 778 098
E-mail: info@cidac.com
Web: www.cidac.es

5. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:

System 3

6. Notified Body: APPLUS / LGAI Technological Center S.A (n° 0370)

has performed type and reaction to fire tests and has issued reports.

In case of the declaration of performance (DoP) concerning a construction product covered by the harmonized standard:

EN 13984:2013

Flexible sheets for waterproofing. Plastic and rubber vapour control layer.

EN 14909:2013

Flexible sheets for waterproofing. Plastic and rubber damp proof courses.

7. Declared Performance:

Harmonized Technical Specification	Characteristic	Test method	Value
EN 13984 EN 14909	Reaction to fire	EN 13501-1	Class E
	Watertightness (2 kPa)	EN 1928	Pass
	Resistance to impact	EN 12691	≥ 300 mm
	Durability (alkali)	EN 1847 EN 12311-2	Pass
EN 13984	Water vapour transmission properties	EN 1931	$\mu = 99800$
	Joint Strength	EN 12317-2	≥ 200 N / 50 mm
	Tensile Strength	EN 12311-2	≥ 6.5 MPa
	Elongation at break	EN 12311-2	≥ 300%
	Tear strength	EN 12310-2	≥ 25 N
	Resistance to water vapour after artificial ageing	EN 1296 EN 1931	Pass
EN 14909	Foldability at Low Temperature	EN 495-5	≤ -30 °C
	Durability (artificial ageing) (2 kPa)	EN 1296 EN 1928	Pass

8. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed by:



Cornellà de Llobregat, Barcelona,

Núria Pamplona Pérez
(Quality Manager)

05/09/2016